



Brass Balls™



SCREW-LOCK BRASS BALL COOLANT NOZZLES FOR CNC LATHES

- Conventional brass ball nozzles available in a variety of orifice sizes and configurations
- Tapped balls can be plugged with setscrew (included), or used with **Extension Tubes**.

DIMENSIONS IN INCHES (except as noted)

Type	Part No.	Nom. Dia "D"	Orifice Dia "D"	Extension "L"	Pkg Qty	Configuration
DRILLED HOLE	BB11004	10 mm	.11	0	5	
	BB11007	10 mm	.16	0	5	
	BB11014	11 mm	.11	0	5	
	BB11015	11 mm	.16	0	5	
	BB11024	12 mm	.16	0	5	
	BB11027	12 mm	.22	0	5	
	BB11037	14 mm	.16	0	5	
	BB11040	14 mm	.22	0	5	
	BB11049	15 mm	.16	0	5	
	BB11052	15 mm	.22	0	5	
	BB11071	22 mm	.16	0	5	
	BB11074	22 mm	.22	0	5	
	BB11083	1/2 inch	.16	0	5	
	BB11086	1/2 inch	.22	0	5	
BB11107	5/8 inch	.16	0	5		
BB11110	5/8 inch	.22	0	5		
TAPPED HOLE	BB11001	10 mm	M6x1.0	0	5	
	BB11016	11 mm	M5x.8	.24	5	
	BB11018	12 mm	M5x.8	.24	5	
	BB11031	14 mm	M6x1.0	.31	5	
	BB11043	15 mm	M6x1.0	.31	5	
	BB11065	22 mm	M6x1.0	.31	5	
	BB11077	1/2 inch	M5x.8	.24	5	
	BB11101	5/8 inch	M6x1.0	.31	5	
ANGLED OUTLET HOLE	BB11012	10 mm	.11	.25	5	
	BB11017	11 mm	.16	.36	5	
	BB11021	12 mm	.16	.36	5	
	BB11034	14 mm	.16	.36	5	
	BB11046	15 mm	.16	.36	5	
	BB11068	22 mm	.16	.36	5	
	BB11080	1/2 inch	.16	.36	5	
	BB11104	5/8 inch	.16	.36	5	



The upper port on this boring bar holder uses an Angled Outlet BrassBall, while the lower port employs a Tapped Hole BrassBall fitted with a Bendable Extension Tube.

Material: Brass

Maximum Pressure: 500 psi (33 bar)

WE RESERVE THE RIGHT TO CHANGE SPECIFICATIONS WITHOUT NOTICE OR OBLIGATION.