




SprayTips



SCREW-IN, BRASS SPRAY TIPS FOR USE IN TAPPED-BALL NOZZLES

- Available in various orifice diameters ■ Ideal for concentrating the coolant stream at the cutting edge
- Angled outlet **SprayTips** enable aiming outside a nozzle's normal range of motion

DIMENSIONS IN INCHES (except as noted)

Type	Part No.	Thread "E"	Orifice Dia. "d"	L	A	"C" Hex	Pkg Qty	Configuration
Straight Outlet	ST16510	M3.5 x .6	.062	.42	.14	3/16	5	
	ST16515	M3.5 x .6	.086	.42	.14	3/16	5	
	ST16520	M4 x .7	.062	.54	.18	3/16	5	
	ST16525	M4 x .7	.086	.54	.18	3/16	5	
	ST16530	M5 x .8	.062	.63	.21	1/4	5	
	ST16535	M5 x .8	.086	.63	.21	1/4	5	
	ST16540	M5 x .8	.117	.63	.21	1/4	5	
	ST16545	M6 x 1.0	.062	.63	.21	1/4	5	
	ST16550	M6 x 1.0	.086	.63	.21	1/4	5	
	ST16555	M6 x 1.0	.117	.63	.21	1/4	5	
	ST16560	M6 x 1.0	.150	.63	.21	1/4	5	
	ST16565	M8 x 1.25	.062	.80	.30	3/8	5	
	ST16570	M8 x 1.25	.086	.80	.30	3/8	5	
	ST16575	M8 x 1.25	.117	.80	.30	3/8	5	
	ST16580	M8 x 1.25	.160	.80	.30	3/8	5	
	ST16585	M8 x 1.25	.220	.80	.30	3/8	5	
	ST16610	1/8NPT/BSPT	.062	.90	.37	1/2	5	
	ST16615	1/8NPT/BSPT	.086	.90	.37	1/2	5	
ST16620	1/8NPT/BSPT	.117	.90	.37	1/2	5		
ST16625	1/8NPT/BSPT	.160	.90	.37	1/2	5		
ST16630	1/8NPT/BSPT	.220	.90	.37	1/2	5		
ST16635	1/8NPT/BSPT	.280	.90	.37	1/2	5		
Angled Outlet	ST16650	M3.5 x .6	.062	.32	.14	3/16	5	
	ST16655	M4 x .7	.062	.36	.18	3/16	5	
	ST16660	M5 x .8	.086	.42	.21	1/4	5	
	ST16665	M6 x 1.0	.086	.42	.21	1/4	5	
	ST16670	M6 x 1.0	.117	.42	.21	1/4	5	



SprayTips can be used in a wide variety of nozzles including; **ScrewBalls, JetBolts, BrassBalls, BlackEyes, TurretJets, JetTubes, SweatJets, CapJets and BugEyes.**

Material: Brass
 Maximum Pressure: 500 psi (33 bar)
 Maximum Operating Temperature: 300°F (150°C)