



ScrewBall™

CONTACT US FOR CUSTOM ORDERS

CONTACT US FOR BULK PRICING



NEW COLORS NOW AVAILABLE

PRESS-IN COOLANT NOZZLE WITH TAPPED HOLE

- Just drill and ream a hole, press in a **ScrewBall**, and you've got an easily aimable coolant nozzle
- Threaded hole can be fitted with an **ExtensionTube** (page 17), **SprayTip** (page 16), or plugged with a setscrew (not included) ■ ±35 degrees of adjustment either side of centerline
- Ideal for quick change toolholders with multiple ports ■ Rated to 150 PSI (10 bar) max
- Choose Black or White body color for best economy

DIMENSIONS IN MILLIMETERS

Part No.	Nominal Dia "D"	Body Color	"A"	Thread "B"	"C"	Prepared Hole Tolerance	Pkg Qty	Configuration
SB09505	8 mm	White	6	M3.5x.6	1.5	H9	5	
SB09506	8 mm	Black	6	M3.5x.6	1.5	H9	5	
SB09507	8 mm	Blue	6	M3.5x.6	1.5	H9	5	
SB09508	8 mm	Yellow	6	M3.5x.6	1.5	H9	5	
SB09509	8 mm	Orange	6	M3.5x.6	1.5	H9	5	
SB09510	10 mm	White	7	M4x.7	2.0	H9	5	
SB09511	10 mm	Black	7	M4x.7	2.0	H9	5	
SB09512	10 mm	Blue	7	M4x.7	2.0	H9	5	
SB09513	10 mm	Yellow	7	M4x.7	2.0	H9	5	
SB09514	10 mm	Orange	7	M4x.7	2.0	H9	5	
SB09520	12 mm	White	8	M5x.8	2.5	H9	5	
SB09521	12 mm	Black	8	M5x.8	2.5	H9	5	
SB09522	12 mm	Blue	8	M5x.8	2.5	H9	5	
SB09523	12 mm	Yellow	8	M5x.8	2.5	H9	5	
SB09524	12 mm	Orange	8	M5x.8	2.5	H9	5	
SB09530	14 mm	White	10	M6x1.0	3.0	H9	5	
SB09531	14 mm	Black	10	M6x1.0	3.0	H9	5	
SB09540	15 mm	Black	6	M6x1.0	3.0	H9	5	
SB09550	16 mm	Black	10	M8x1.25	3.0	H9	5	

Material: Body: Acetal Ball: Stainless Steel Maximum Operating Temperature: 160°F (70°C)

Maximum Pressure: 150 PSI (10 bar)

WE RESERVE THE RIGHT TO CHANGE SPECIFICATIONS WITHOUT NOTICE OR OBLIGATION.